


STARTER TRAC

Vinyl Corp

Designed by Vinyl Corp. as a base support starter strip with drip leg for exterior insulated wall. Perforated flange allows matrix to easily flow thru and anchor to substrate. Drip leg moves moisture away from openings or foundation wall. All have Vinyl Corp.'s patented "Key Lock" splice to reinforce butt joints. Caulk all Intersections, Butt Joints and Ends.

ITEM # 716310	1 1/2" X 10' CBS150-332
# 716312	2" X 10' CBS200-332
# 716318	1" X 10' CBS100-16D (WITH DRIP EDGE)
# 716320	1 1/2" X 10' CBS150-16D (WITH DRIP EDGE)
# 716322	2" X 10' CBS200-16D (WITH DRIP EDGE)
# 716330	1" X 10' CBS100-16W (WITH WEEP HOLES)
# 716332	1 1/2" X 10' CBS150-16WB (WITH WEEP HOLES)
# 716334	2" X 10' CBS200-16WB (WITH WEEP HOLES)

**1" THICK SOFFIT VENT**

Vinyl Corp

One-piece Soffit Vent, designed for soffit board, and may be combined with Starter Strip/Casing Beads or DEFS Casing Beads. Vinyl Corp.'s., "Vent Clips" are provided to connect Soffit Vent and assist in alignment. Vent area: 4 square inches per lineal ft.

ITEM # 716340	CBS100-200V	10' LONG
---------------	-------------	----------

ACCESS DOORS**ENTRY DOORS****S20 2'6"X3' GALVANIZED STEEL ROOF HATCH**

Bilco



Type S, 36" x 30" (914mm x 762mm), the easy one-hand operation to the fully open or close position provides the ladder user the security of having one hand firmly on the ladder at all times. Available in galvanized steel or aluminum construction.

ITEM # 831360	(HINGED ON 2'6" SIDE)
---------------	-----------------------

THERMAL/WATERPROOFING/ DOORS

www.stetsonbuildingproducts.com



ENTRY DOORS

RBS-1 ROOF HATCH 3'0"X2'6" GALVANIZED STEEL PRIME PAINTED

Milcor

16 gauge prime-painted galvanized steel, or .90 aluminum with a 12" high curb, integral counterflashing, 3 1/2" wide mounting flanges with pre-drilled holes, and 1" exterior fiberboard insulation. Milcor Roof Hatches have torsion bar spring mounted within the confines of the cover. This provides a virtually obstruction-free hatch opening.

ITEM # 831342

ACCESS DOORS

DW ACCESS DOOR WITH CAM LOCK

Milcor

Milcor DW Access Doors provide critical service access in drywall Ceilings or walls. Door style is flush with provision to conceal Flange with drywall cement. 16-gauge steel frame with 14-gauge door panel. Galvanized steel drywall bead. Steel is chemically bonded with a prime coat of baked-on electrostatic powder. Flush, screwdriver-operated with steel cam.

ITEM	# 831200	8"X8"
	# 831202	10"X10"
	# 831206	12"X12"
	# 831210	14"X14"
	# 831212	16"X16"
	# 831214	18"X18"
	# 831216	22"X22"
	# 831218	24"X24"

OTHER SIZES ARE AVAILABLE BY SPECIAL ORDER. PLEASE CALL FOR MORE INFORMATION.



UNIVERSAL FIRE RATED ACCESS DOOR WITH KEYED LOCK (WALL OR CEILING)

Milcor

The Milcor Fire Rated Door may be specified with the confidence for service access to utilities in the walls of stairwells, shafts, corridors and all other wall areas where fire ratings are stipulated by code requirements. The same protection is provided when the universal fire rated door is installed in fire rated ceilings. Fire Rated carries both the UL and CUL 1 1/2 hour, Class B fire rating as well as the Warnock Hersey Label for three-hours noncombustible floor/ceiling systems. Prime painted steel, 14 gauge frame with 20 gauge door panel. 2" mineral fiber insulation sandwiched between inner and outdoor panel. Steel is chemically bonded with a prime coat of baked on electrostatic powder. Continuous type hinge. Flush mounted paddle latch and locking system with flush, key-operated cylinder lock with two keys. All doors have interior latch release mechanism.

ITEM	# 831224	8"X8"
	# 831226	12"X12"
	# 831228	14"X14"
	# 831232	16"X16"
	# 831234	18"X18"
	# 831236	22"X30"
	# 831238	22"X36"
	# 831240	24"X24"
	# 831244	24"X36"
	# 831246	24"X48"
	# 831248	30"X30"
	# 831250	32"X32"
	# 831252	36"X36"

THERMAL/WATERPROOFING/ DOORS

www.stetsonbuildingproducts.com



M ACCESS DOOR WITH CAM LOCK

Milcor

Ideally suited for new installation or remodeling, the Milcor M access door can be used in masonry, tile, wood, or other wall surfaces. Its exposed, three quarters of an inch frame flange adds to the rigidity of the unit, while hiding the rough wall opening. The style M is a flush mounted door. Prime-painted, 14 gauge steel frame and door panel. Flush, screwdriver-operated with steel cam lock. Cylinder lock with two keys furnished is also available. Available by special order in a Stainless Steel finish or custom sizes.

ITEM	# 831264	6"X6"
	# 831266	8"X8"
	# 831270	10"X10"
	# 831272	12"X12"
	# 831273	12"X12" (CYLINDER LOCK)
	# 831274	12"X16"
	# 831278	12"X24"
	# 831280	14"X14"
	# 831282	16"X16"
	# 831284	16"X20"
	# 831285	16"X24"
	# 831286	18"X18"
	# 831288	18"X24"
	# 831290	20"X24"
	# 831292	20"X30"
	# 831294	22"X22"
	# 831296	22"X36"
	# 831300	24"X24"
	# 831302	24"X24" (CYLINDER LOCK)
	# 831304	24"X30"
	# 831306	24"X36"
	# 831308	24"X48"
	# 831310	30"X30"
	# 831312	36"X36"

18X18 K PLASTER ACCESS DOOR WITH CAM LOCK

Milcor



The Milcor K access door meets the specific needs of the plaster construction-for an easy-to-install unit with an attractive finished appearance. Usable in either walls or ceilings. 16 gauge steel frame with 14 gauge door panel and 22 gauge galvanized casing beads. Flush, screwdriver-operated with steel cam lock. Other sizes are available by special order.

ITEM # 831330

OTHER SIZES AVAILABLE. PLEASE CALL FOR DETAILS.

**OTHER ACCESS DOOR STYLES
AVAILABLE BY SPECIAL ORDER.
PLEASE CALL FOR YOUR
JOB SPECIFICATION NEEDS**